



# LL5817 THRU LL5819

## 1.0 AMP. Surface Mount Schottky Barrier Rectifiers




Voltage Range  
20 to 40 Volts  
Current  
1.0 Ampere

### MELF

### Features

- ✧ Surge overload ratings to 25 amperes peak
- ✧ Ideal for printed circuit board
- ✧ Reliable low cost construction utilizing molded plastic technique results in inexpensive product
- ✧ Mounting position: Any
- ✧ Weight: 0.12 gram



Dimensions in inches and (millimeters)

### Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%


Type Number	Symbol	LL5817	LL5818	LL5819	Units
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	20	30	40	V
Maximum RMS Voltage	$V_{RMS}$	14	21	28	V
Maximum DC Blocking Voltage	$V_{DC}$	20	30	40	V
Maximum Average Forward Rectified Current @ $T_L = 90^\circ\text{C}$	$I_{(AV)}$	1.0			A
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	$I_{FSM}$	25			A
Maximum Instantaneous Forward Voltage @ 1.0A	$V_F$	0.450	0.550	0.600	V
Maximum Instantaneous Forward Voltage @ 3.0A	$V_F$	0.750	0.875	0.900	V
Maximum DC Reverse Current @ $T_A=25^\circ\text{C}$ at Rated DC Blocking Voltage @ $T_A=100^\circ\text{C}$	$I_R$	1.0 10			mA mA
Typical Thermal Resistance (Note 1)	$R\theta_{JA}$	80			$^\circ\text{C}/\text{W}$
Typical Junction Capacitance ( Note 2 )	$C_j$	110			pF
Operating and Storage Temperature Range	$T_J, T_{STG}$	- 65 to + 125 / - 65 to + 150			$^\circ\text{C}$

Notes: 1. Thermal Resistance Junction to Ambient


2. Measured at 1 MHz and Applied Reverse Voltage of 4.0 Volts D.C.

## RATINGS AND CHARACTERISTIC CURVES (LL5817 THRU LL5819)


**FIG.1- MAXIMUM FORWARD CURRENT DERATING CURVE**



**FIG.2- TYPICAL JUNCTION CAPACITANCE**



**FIG.3- TYPICAL FORWARD CHARACTERISTICS**



**FIG.4- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT**

